

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 April 2001 (12.04.2001)

PCT

(10) International Publication Number  
**WO 01/25414 A1**

(51) International Patent Classification: C12N 11/10,  
B01J 13/02

(74) Agent: TAYLOR, Douglas, J.; General Mills, Inc., P.O.  
Box 1113, Minneapolis, MN 55440 (US).

(21) International Application Number: PCT/US00/22529

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 17 August 2000 (17.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/410,017 1 October 1999 (01.10.1999) US

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): GENERAL MILLS, INC. [—/US]; Number One General Mills Boulevard, Minneapolis, MN 55426 (US).

**Published:**

— With international search report.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): VAN LENDERICH, Bernhard, H. [DE/US]; 18005 33rd Place N., Plymouth, MN 55447 (US).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: ENCAPSULATION OF SENSITIVE COMPONENTS INTO A MATRIX TO OBTAIN DISCRETE SHELF-STABLE PARTICLES

(57) Abstract: A solid active, sensitive encapsulant component is admixed with at least one plasticizable matrix material, a matrix component which is substantially non-plasticizable at temperatures lower than the decomposition temperature of the encapsulant and which increases the rate of release of the encapsulant from the matrix, and a liquid plasticizer, to obtain a formable, extrudable, cuttable mixture or dough.

WO 01/25414 A1

**THIS PAGE BLANK (USPTO)**

ENCAPSULATION OF SENSITIVE  
COMPONENTS INTO A MATRIX TO OBTAIN DISCRETE  
SHELF-STABLE PARTICLES

FIELD OF THE INVENTION

5           The present invention relates to a continuous process for producing shelf-stable, controlled release, discrete, solid particles which contain an encapsulated and/or embedded component such as a heat sensitive or readily oxidizable pharmaceutically, biologically, or nutritionally active component.

BACKGROUND OF THE INVENTION

10           In encapsulating a component in a matrix, the matrix material is generally heated to a sufficiently high temperature to provide a plasticized mass which facilitates embedding or coating of the component. Upon cooling, the matrix material hardens or becomes solidified and protects the encapsulant from undesirable or premature reaction. However, heating of the matrix to plasticize it  
15           or to form a melt may deleteriously affect or decompose the encapsulant as well as the matrix material. Additionally, the mixing or high shear used to disperse the encapsulant uniformly throughout the plasticized matrix material may likewise adversely affect the matrix material or encapsulant. Furthermore, the use of high temperatures to plasticize or melt the matrix material may cause  
20           evaporation and loss of the encapsulant. The addition of liquids to the matrix material to reduce its viscosity and to facilitate mixing may require excessive drying or evaporation of the plasticizing liquid for the attainment of a formable composition capable of being formed into discrete, substantially uniform pieces. Furthermore, removal of the plasticizing liquid may adversely expand the  
25           product, decrease its density, and make the encapsulated component more susceptible to attack or more easily released. These problems involved with the removal of liquid encapsulant are even more pronounced when the commercially available form of the encapsulant is dissolved or dispersed in a liquid. While the

liquid may be removed prior to encapsulation by drying, expensive methods such as spray drying, freeze drying, and vacuum drying are generally needed to avoid decomposition of the encapsulant by drying at elevated temperatures.

Additionally, the dried encapsulants may be dusty and may cause adverse health effects when handled in concentrated forms or when inhaled.

The production of expanded products is disclosed in European patent publication nos. EP 0465364 A1 (published January 8, 1992) and EP 0462012 A2 (published December 18, 1991), U. S. patent no. 3,962,416 to Katzen and U. S. patent no. 3,786,123 to Katzen. The two European patent publications disclose the production of an anti-obesity food and a method for making it by extrusion of starches with fatty acids into an expanded product having densities between 0.1 and 0.3 g/cm<sup>3</sup>. U. S. patent no. 3,962,416 to Katzen discloses an expanded product which contains at least one nutrient and one gelatinized starch.

U. S. patent no. 3,786,123 to Katzen discloses a method for producing encapsulated nutrients using extrusion temperatures of between 250°F and 400°F and extrusion pressures of between 200 psi to 2500 psi. A high protein encapsulating agent containing up to 40% starch may be used. The starch is gelatinized and extruded into an expanded product.

However, in producing a product having controlled release or delayed release, excessive expansion or puffing may result in too rapid release properties or may undesirably expose an encapsulant to destructive reactions. For example, an edible composition for delivering encapsulated pharmaceutically or nutritionally active components or for a non-edible agricultural product for delivering biocides or herbicides, it is desirable that the products have a substantially spherical shape and a high density. Such products exhibit a substantially low ratio between surface area and volume and thus minimize or prevent surface related destructive reactions that occur upon exposure to air or

oxygen and light. The spherical shapes and high densities also minimize the surface which would be available to expose embedded material which is not encapsulated. Furthermore, for edible products for delivering pharmaceutically or nutritionally active components, it is desirable that the products are capable of being consumed or swallowed without chewing or substantially no chewing. Avoiding the need for mastication, further assures that the products reach the digestive tract without substantial enzymatic hydrolysis in the mouth. Furthermore, it helps to control or reduce dissolution of the product in gastric juice and to control the release of the embedded or encapsulated components in the stomach and/or in the intestine.

International patent publication no. WO 92/00130 (published January 9, 1992) discloses a continuous process for obtaining an encapsulated, biologically active product in a starchy matrix. A biologically active agent and starch are mixed before extrusion and extruded as a blend, with the encapsulant or biologically active agent being heated together with the starch. Alternatively, a core material to be encapsulated may be added and blended with an aqueous dispersion of starch after the starch and water have been subjected to an elevated temperature sufficient to gelatinize the starch. The extrusion process, it is disclosed, exposes the mix to high shear mechanical action at a temperature above the gelatinization temperature of the starch. The use of extrusion barrel temperatures of between about 58°C and 98°C are disclosed. While these barrel temperatures may be above the gelatinization temperature of starch, the extruder utilized has barrel sections that are only three l/d long. The screw speeds utilized, between 400 rpm and 200 rpm, result in a very short residence time of the blend inside the extruder and barely allow heating up of the starch water mix. As a result, the temperatures obtained are generally too low to obtain substantial gelatinization of native starches. Additionally, the barrel temperatures used are particularly too low for substantial gelatinization of high amylose starch which

generally gelatinizes at temperatures substantially above 100°C, for example at 125°C. The use of extrusion barrel temperatures which are not sufficiently high to substantially or completely gelatinize the starch may not form a sufficiently continuous, plasticized and homogeneous matrix for effective embedding or encapsulation.

In addition, the use of relatively low extrusion temperatures, high speed mixing, and a high viscosity starch composition generally requires a high mechanical energy input. High shear is directly related to high specific mechanical energy, which in turn increases the molecular destructurization and dextrinization of starch. Breakdown of the starch molecules, and in particular the amylopectin, increases the solubility of the extruded starch composition in aqueous systems as described in P. Colonna, et al., "Extrusion Cooking of Starch & Starchy Products," Extrusion Cooking, C. Mercier, et al. pp. 247-319, AACC, St. Paul, Minn. (1989) and F. Meuser, et al, "A Systems Analytical Approach To Extrusion," Food Extrusion Science & Technology, ed. J. Kokini, Dekker Publ., pp. 619-630 (1992). Increased solubility of the extruded starch in aqueous systems decreases the stability of the product against moisture and subsequently diminishes or shortens the protection and controlled release of the embedded or encapsulated substances. In addition, subjecting the encapsulant to the same high shear and high temperature conditions to which the starch is subjected may adversely affect the encapsulant by at least partially destroying it or decomposing it into unknown solid or volatile substances.

Pregelatinized starch is used in numerous applications in the food industry as a swelling agent and for accelerated and extended water absorption in foods such as soups, sauces, instant puddings, baby food, and thickening agents. However, it has been found that the use of pregelatinized starch or the use of starch as the only matrix material during extrusion cooking generally results in a matrix which releases the encapsulant too quickly. It has been found that the

penetration of water into a pure starch matrix causes early release of the encapsulant into the environment. Generally the time to release 100% of the encapsulant is too short to provide a desirable time-release or controlled-release which is effective for delivering the encapsulant at a desired location or time.

5 International patent publication no. WO 95/26752 (published October 12, 1995) discloses the production of a food product for the enteric supply of a fatty acid, a fatty acid containing substance, an amino acid, or an amino acid containing substance by at least partially complexing the fatty acid or amino acid in the amylose helix of starch to mask the acid. The product may contain one or  
10 more flavors and colors, fat soluble substances, anti-oxidants, or pharmacologically effective substances. The components may be first dry mixed and subsequently fed into an extruder where they are substantially mixed and subsequently heated above the gelatinization temperature of the starch to obtain an elasticized mass which is extruded and formed into pellets. However, heat-  
15 sensitive components would be destroyed during the heating step.

International patent publication no. WO 85/04074 to Flashinski, et al. (published September 26, 1985) discloses an insect bait containing an insect-controlling material in a gelatinized starch matrix. The bait is made by coextruding starch with the insect-controlling material at temperature and  
20 pressure conditions sufficient to cook and gelatinize the starch. Alternatively, a pregelatinized starch may be mixed with the insect-controlling material and water to form a gel. In the formation of the insect bait by mixing and extruding the components, it is disclosed, it is essential to utilize additives, including the insecticides and repellants which will withstand the extrusion temperatures of  
25 starch without the degradation or vaporization. The extrusion temperatures of the insect-bait mixture, depending upon the starch content and other additives, ranges between about 160 to about 310°F at pressures of from about 300 through 800 psi.

U. S. patent no. 5,183,690 to Carr, et al. discloses a continuous process for imparting predetermined release properties to an encapsulated biologically active agent in a matrix of starchy material. The starchy material, an active agent, and water are continuously blended in an ingredient stream wherein the starchy material is at a solids concentration of at least 40%. The ingredients stream is continuously extruded as an extrudate and the extrudate is continuously recovered. The conditions of blending, extruding, and recovering are preselected to yield the predetermined release properties. The temperature is elevated to at least about 65°C to effect gelatinization of starch and assure an essentially molecular dispersion of the starch in the water. Alternatively, the core material to be encapsulated is added and blended with the aqueous dispersion of starch after the starch and water has been subjected to an elevated temperature sufficient to gelatinize the starch. In this embodiment the aqueous starch stream containing gelatinized starch may be lowered to a temperature as low as about 25°C before the core material to be encapsulated is added and subjected to high-shear mechanical action. Under such low temperature conditions of admixture it is disclosed, the activity of sensitive biological material, such as bacteria and viruses, is preserved and loss of volatile organic materials is minimized. The rate of swelling of the products in water and the rate of release of active agents are controlled by altering the amount of water present in the starch-agent-water blend during processing. As the amount of water is decreased, both the swelling rate and the release rate increase. The rate of swelling of the products in water and the rate of release of active agent are also controlled by passage of the extrudate containing starch-agent-water through an exit die of various dimensions. As the exit die is reduced in size, both the rate and extent of swelling increase and the rate of release of agent increases.

Copending U.S. application serial no. 09/269,763, filed April 12, 1999, which is a 35 U.S.C. 371 U.S. National Stage application of International Patent



Application No. PCT/US97/18984, filed October 27, 1997 in the name of Bernhard H. Van Lengerich, and published under International Publication No. WO 98/18610 on May 7, 1998, the disclosures of which are herein incorporated by reference in their entireties, disclose a controlled release particulate composition which contains a hydrophobic component for controlling the release of an encapsulated and/or embedded active component from a plasticized matrix.

High water binding capacity agents may also be used to delay or control the release of the encapsulant from the matrix. A high amount of plasticizer is employed to facilitate plasticization of the matrix material at low shear and is then reduced prior to adding the encapsulant to facilitate subsequent forming and to reduce post extrusion drying. The controlled release or delayed release composition may be produced without substantial expansion of the matrix material to thereby avoid production of a low density product which prematurely or too rapidly releases the encapsulant or the embedded component.

The present invention provides a process for producing discrete, particulate, shelf-stable encapsulated heat-sensitive components from solids, such as powders, or from solutions or dispersions of the component without the need for predrying of the solution or dispersion. The particulates may be produced at low temperatures without substantial heating or without substantial gelatinization of starch to avoid thermal destruction of the heat-sensitive components, and to avoid substantial expansion. An extrudable, formable, cuttable, mixture or dough may be obtained continuously without the need for removing or evaporating liquid plasticizer prior to extrusion or forming. The processes of the present invention may be used for the continuous production of an edible composition for delivering pharmaceutically or nutritionally active components, such as enzymes or live microorganisms, or for the production of an agricultural product for the controlled release of biocides, herbicides, fertilizers,

growth stimulators, pesticides, or products for other uses such as, for example, detergents which release chemical and/or biological agents.

### SUMMARY OF THE INVENTION

5 The present invention provides a continuous process for producing controlled release, discrete, solid particles which contain an encapsulated and/or embedded component. The encapsulant may be a solid and/or liquid encapsulant component. The particles comprise a matrix material in which the active component is encapsulated or embedded. The matrix material is plasticizable by a liquid plasticizer, or by the liquid of a liquid encapsulant component, under low  
10 shear and low temperature conditions which are sufficiently low so as to avoid substantial decomposition, destruction, or evaporation of the encapsulant. A formable, extrudable, cuttable mixture or dough is obtained by admixing ingredients comprising at least one plasticizable matrix material, the solid and/or liquid encapsulant component, and at least one component for controlling the  
15 rate of release of the encapsulant. In embodiments of the invention, solid components which are substantially non-plasticizable at temperatures lower than the decomposition temperature of the heat sensitive encapsulant are used to increase the rate of release of the encapsulant from the matrix.

The admixing is performed under low shear and low temperature  
20 conditions to plasticize the plasticizable material without substantially destroying the encapsulant to obtain a substantially homogeneous plasticized, viscoelastic, formable mixture. The formable mixture may be obtained without cooking or without gelatinizing the matrix ingredients. The plasticized matrix material in the formable mixture may become glassy upon drying, even though it was not  
25 cooked or substantially gelatinized during low temperature plasticization to obtain the formable mixture.

In embodiments of the invention, the encapsulant is employed in solid, particularly powdered, form. In other embodiments, a liquid encapsulant component comprising an encapsulant and a liquid that acts as plasticizer is employed. The liquid encapsulant component provides at least a substantial portion of the liquid plasticizer for forming the plasticized mixture.

Extrusion of the plasticized mixture may be performed without substantial expansion of the product thereby providing a high density product. The process of the present invention may be used to encapsulate heat sensitive components or readily oxidizable components, for example, pharmaceutically or biologically or nutritionally active components, without substantially destroying their activity. Examples of these may be enzymes, microorganisms or vitamins. The products of the present invention may be edible for direct consumption or for incorporation into or addition to human food products or animal feed. In other embodiments of the invention, products, such as chemical or agricultural products such as pesticides, herbicides, fungicides, insecticides, rodenticides, or other products like detergents or flavorants, fragrances, and the like may be advantageously embedded or encapsulated to control or delay their release from their surrounding matrix.

In embodiments of the present invention, at least one additional ingredient or component may be used to control the release properties and hardness of the final product. The additional component may manage, control or affect the flow, diffusion or distribution of water or aqueous-based compositions into and within the final product particles. The additional ingredient or component for controlling the rate of release of the encapsulant may be a hydrophobic agent such as polyethylene, polyurethane, polypropylene, polyvinylchloride, polyvinylacetate, a fat, oil, wax, fatty acid, or emulsifier which increases the hydrophobicity of the matrix. The increased hydrophobicity helps to prevent or delays penetration of water or gastric juice into the matrix. Other ingredients

which may be used to control the rate of the release are components which have a high water binding capacity which delay or prevent a fast dissolving of the matrix and thereby delay the release of the encapsulant into the matrix.

Exemplary of high water binding capacity components which may be used are proteins, such as wheat gluten, gelatin, and casein, hydrocolloid gums, and the like.

In embodiments of the invention, matrix components may be added to increase the rate of release of the encapsulant. These release rate increasing components may dissolve more readily in water than does another matrix material. Upon dissolution, permeability of the particles is increased, thereby increasing access to the encapsulant by the penetrating aqueous-based solvent. The release rate increasing components may be insoluble or substantially insoluble in the plasticizer such as water, or inert and may serve to disrupt the matrix formed by the plasticizable material to increase its porosity or microporosity, thereby increasing access to the encapsulant by the penetrating solvent.

In accordance with the method of the present invention, at least one plasticizable, matrix-forming material such as durum wheat or semolina, vital wheat gluten, pregelatinized starch, flour, flour from cookies or crackers or flour from cookie or cracker type products, pentosans, or hydrocolloids which is at least substantially plasticizable by the liquid plasticizer or by the liquid encapsulant component at a temperature of less than about 50°C is admixed with the solid encapsulant and/or liquid encapsulant component to obtain a formable mixture. The solid, substantially non-plasticizable matrix component may be preblended or dry blended with plasticizable matrix material, solid encapsulants, and other dry or powdered components for admixture with the plasticizer, or they may be separately added.

Where a liquid encapsulant component is employed, an additional amount of a plasticizer such as water may be added to reduce or adjust viscosity of the mixture without the need to subsequently remove plasticizer prior to extrusion or forming.

5           The encapsulant is admixed with the plasticizable matrix material under low temperature, low shear mixing conditions to distribute, coat, embed, or encapsulate the added active ingredient in the plasticized matrix material. Mixing is continued towards the extruder die while optionally adjusting the product temperature for sufficient formability.

10           The admixture is extruded through extrusion dies and cut or otherwise formed into pieces or pellets with no or substantially no expansion of the extrudate. The extrudate or pieces may then be dried and then surface treated with a film-building substance to coat the extruded pellets or pieces. The film-building substance may also contain additional components that delay or prevent  
15           the access of light, oxygen, and/or water to the matrix. In embodiments of the invention, one or more solid, pharmaceutically, nutritionally, biologically or, chemically active ingredients may be admixed with the plasticizable matrix material and one or more liquid encapsulant components. The solid encapsulants employed in the present invention may be precoated with a coating material such  
20           as shellac, zein, chitosan, chitin, an emulsifier or the like to further control the release properties of the encapsulant from the matrix material.

          The products of the present invention may be in the form of discrete particles, pellets, or tablets. They may be spherical in shape, curvilinear or lens-shaped, flat discs, oval shaped, or the like. The diameter of the particles may  
25           range up to about 7 mm, for example from about 0.3 mm to about 7 mm and the l/d ratio may be from about 0.1 to about 10. In embodiments of the invention, the diameter of the particles may be from about 0.15 mm to about 4 mm,

preferably from about 0.25 mm to about 1.0 mm. The specific density of the pellets or particles may be from about 800 g/liter to about 1500 g/liter.

5 In embodiments of the invention, the amount of the matrix component which is substantially non-plasticizable, such as non-gelatinized starch, is at least about 10% by weight, preferably at least about 25% by weight, based upon the total weight of the at least one plasticizable matrix material and the matrix component which is substantially non-plasticizable.

10 The total amount of plasticizer, such as water, admixed with the plasticizable matrix material, such as semolina or flour from ground cookies or ground crackers, and the substantially non-plasticizable matrix component, such as non-gelatinized starch or other, at room temperature inert materials, to form a plasticized mass may range up to about 90% by weight, for example from about 10% by weight to about 70% by weight, generally from about 20% by weight to about 50% by weight, preferably from about 25% by weight to about 45% by weight, based upon the total weight of the plasticizable matrix material such as semolina or flour from ground cookies or crackers, the substantially non-plasticizable matrix component, such as non-gelatinized starch, and the added plasticizer.

20 The liquid plasticizer content of the liquid encapsulant component may be at least about 35% by weight, generally at least about 50% by weight, based upon the weight of the liquid encapsulant component. The amount of additional ingredients used to control the rate of release of the active component may range up to about 70% by weight, preferably from about 5% by weight to about 50% by weight, most preferably from about 10% by weight to about 35% by weight based upon the weight of the plasticizable matrix material such as semolina.

25 The amount of the active component or encapsulant which may be encapsulated or embedded into the matrix may be from about 1% by weight to about 85% by weight, preferably from about 3% by weight to about 50% by

weight, most preferably from about 5% by weight to about 30% by weight, based upon the total weight of the plasticizable matrix ingredient, such as semolina and the substantially non-plasticizable matrix ingredient such as non-gelatinized starch.

5

#### DETAILED DESCRIPTION OF THE INVENTION

A solid encapsulant and/or a liquid encapsulant component which contains an active, sensitive encapsulant dissolved or dispersed in a liquid plasticizer is admixed with a plasticizable matrix material which is plasticizable by the liquid plasticizer to encapsulate the active encapsulant at a low temperature and under low shear conditions. In embodiments of the invention, solid components which are substantially non-plasticizable at temperatures lower than the decomposition temperature of the heat sensitive encapsulant are used to increase the rate of release of the encapsulant from the matrix. The plasticizable matrix material is plasticizable and is plasticized by the liquid plasticizer but the substantially non-plasticizable matrix component is substantially non-plasticizable and is not plasticized by the liquid plasticizer generally at a temperature of less than about 50°C, preferably less than 40°C, most preferably less than about 35°C, for example at room temperature. A formable mixture is obtained without substantially gelatinizing or cooking the plasticizable matrix material or the substantially non-plasticizable matrix component.

Oil may be optionally added to the matrix material prior to or after adding the solid and/or liquid encapsulant. In an embodiment of the invention, one or more plasticizable matrix materials and optional dry ingredients may be first dry mixed and subsequently mixed with oil. After mixing with oil, the solid encapsulant and/or the liquid encapsulant component may be admixed into the matrix/oil preblend to obtain a mix.

Before the mix forms a dough, it may be transferred to a compressing section of an extruder screw and extruded into discrete particles. The active component may be encapsulated and/or embedded in the plasticizable matrix component or material in a batch, semi-continuous, or continuous process to produce discrete, solid particles.

In embodiments of the invention, the liquid content of the liquid encapsulant component provides substantially all or completely all of the liquid plasticizer needed to plasticize the matrix component to obtain a formable, extrudable, cuttable, mixture or dough. Removal of liquid plasticizer prior to extrusion to adjust the viscosity of the mixture for formability is not needed.

Release of an active component from the matrix may be purposely delayed or controlled over time so that the active component is delivered when and where it is needed to perform its intended function. The release of an active component from the matrix may be controlled by an additional ingredient or additive which affects the hydrophobicity of the matrix or particle, the water binding capacity of the matrix or particle, the solubility, porosity or microporosity of the matrix material or particle, or the glass transition ( $T_g$ ) of the matrix material or particle. Pre-process coating of an encapsulant prior to admixing it into the matrix material, extrusion process conditions, the final shape of the discrete particles, and optional coating of the discrete particles may also be used to control the release of an active component from the matrix material.

The process of the present invention advantageously at least substantially uniformly distributes, embeds, or encapsulates an active component in the matrix material. The encapsulation process enhances stability of the active component against moist heat during further processing of the encapsulated active component, such as during pelletizing or extrusion. The active components may be dispersed in the matrix material on a microscopic or molecular level. Active components which are dispersed on a molecular level may provide a higher



bioavailability when released, as compared to their crystalline forms. The active components in the final product may be encapsulated or embedded in either a shelf-stable solid form or liquid form.

5 The encapsulants and encapsulated products of the present invention may be edible such as pharmaceutically or biologically or nutritionally active components, or flavors or fragrances or they may be inedible compositions such as a detergent, herbicide, fungicide, pesticide, insecticide, or rodenticide, a home or personal care product and the like. They may be used for human or animal consumption. The encapsulants and encapsulated products may be suspensions  
10 of microorganisms in water, pharmaceutically active compounds, vitamins or minerals in solid, particularly powder or crystalline, form, and suspensions or dispersions or emulsions or solutions of vitamins, enzymes, minerals or trace elements in water or other liquids. Release of an encapsulant from the matrix material may also be controlled by the use of a film or coating upon the discrete,  
15 solid matrix-encapsulated particles.

The plasticizable matrix material which is plasticizable at low temperatures by the liquid plasticizer or by the liquid of the liquid encapsulant component may be a plasticizable biopolymer such as a carbohydrate, such as a modified or pregelatinized starch or cyclodextrin, or polymer such as  
20 polyvinylpyrrolidone or other non-hydrophobic polymers such as copolymers of N-vinylpyrrolidone (NVP) and vinylacetate, polyvinyl alcohol, cellulose esters, cellulose ethers, and polyethylene glycol, pentosans, hydrocolloids such as carragenan, alginates, or gum arabic, wheat gluten, such as vital wheat gluten or isolated gluten, vegetable or dairy proteins such as protein from soy or milk, and  
25 mixtures thereof. Exemplary starches which may be used in the present invention are modified starches or pregelatinized starches derived from corn, wheat, rice, potato, tapioca, or high amylose starch. Sources of starch which may

be used also include flours from grains such as corn, wheat, durum wheat, rice, barley, oat, or rye, and mixtures thereof.

Preferred plasticizable matrix materials for edible products of the present invention are high gluten content flours, gluten from wheat, durum wheat or semolina, pregelatinized starch, pentosans, hydrocolloids, and mixtures thereof. For easier distribution or dispersibility in liquids such as water and oil, finely ground or powdered cookies or crackers, or ground cookie-like or cracker-like products may be employed as a matrix material. The ground cookie or cracker products may be obtained by grinding or milling cookies or crackers to obtain a particle size distribution similar to that of a flour.

Durum products or ingredients which may be used in the present invention include durum semolina, durum granular, durum flour and mixtures thereof. Durum semolina is preferred. Durum semolina is the purified or isolated middlings of durum wheat prepared by grinding and bolting cleaned durum wheat to such fineness that when tested by the method prescribed in 21 CFR § 137.300(b)(2), it all passes through a No. 20 U.S. sieve, but not more than 3 percent passes through a No. 100 U.S. sieve. The semolina is freed from bran coat or bran coat and germ to such an extent that the percent of ash therein, calculated to a moisture-free basis, is not more than 0.92 percent. The durum granular product is a semolina to which flour has been added so that about 7% passes through the No. 100 U.S. sieve. Durum flour has not less than 98 percent passing through the No. 70 U.S. sieve.

Additional matrix components which may be used include solid components which are substantially non-plasticizable at temperatures lower than the decomposition temperature of the heat sensitive encapsulant. The substantially non-plasticizable matrix components may be used to increase the rate of release of encapsulant from the matrix. Exemplary of such substantially non-plasticizable matrix components are at least substantially non-gelatinized

starch, carbohydrates which have a lower molecular weight than starches, bulking agents, fiber, or other, inert materials, such as cellulose, or hemi-cellulose. The lower molecular weight matrix components tend to dissolve or disperse more readily than does the starch and increase the penetrability, porosity or microporosity of the matrix. As a result, access by the dissolution medium, such as water or acid, to the encapsulant is increased thereby permitting quicker release of the encapsulant from the matrix material. Examples of carbohydrates other than starch which may be used are sugars, such as mono- and di-saccharides, and starch hydrolyzate products such as dextrans or syrups with dextrose equivalent values (DE values) ranging from about 2 to about 99, or from about 5 to 98, and mixtures thereof. The release rate increasing components may be insoluble or substantially insoluble in the plasticizer such as water, or inert and may serve to disrupt the matrix formed by the plasticizable material to increase its porosity or microporosity, thereby increasing access to the encapsulant by the penetrating solvent.

In embodiments of the invention, the plasticizable matrix material is plasticizable by the plasticizer, such as water, into a plasticized, formable mixture without undergoing substantial cooking or gelatinization and without forming a glassy matrix. However, the plasticized, formable matrix material may form a glassy matrix upon drying. Inclusion of a substantially non-plasticizable matrix component tends to disrupt the glassy matrix and increase the rate of release of the encapsulant from the matrix. For example, semolina may be plasticized by water without cooking or gelatinization at room temperature and may then form a glass or glassy matrix upon drying. Inclusion of a matrix component which is substantially non-plasticizable at room temperature, such as non-gelatinized starch, substantially non-gelatinized starch, an inert or bulky material, or carbohydrates which have a lower molecular weight than starches may disrupt, weaken, or soften the glassy matrix formed upon drying the

formable mixture. The disruption, weakening or softening of the glassy matrix or increased porosity or microporosity of the glassy matrix may increase the penetrability of the matrix and increase the rate of release of the encapsulant. The substantially non-plasticizable matrix component such as substantially non-gelatinized starch may introduce discontinuity into the continuous phase of a plasticized matrix material, such as a gluten network thereby increasing penetratability of the matrix and a quicker encapsulant release rate.

The matrix material is used in an effective encapsulating amount. In embodiments of the present invention, the matrix material content, such as the semolina content or cookie or cracker flour content of the particles may be at least about 30% by weight, for example from about 60% by weight to about 95% by weight, based upon the weight of the final product.

In embodiments of the invention, the plasticizable matrix material is employed in an amount which is sufficiently high to enable formation of a pellet from the plasticized matrix material. For example, if vital wheat gluten or isolated gluten is the only plasticizable matrix material it should generally be employed in an amount of at least about 1% by weight, preferably at least about 2% by weight, more preferably about 10% by weight or more, based upon the total dry weight or total dry matter of the extrudate or final product.

In embodiments where the plasticizable matrix material is a source of gluten, such as semolina or wheat flour, the matrix material may be employed in such an amount so as to provide gluten in an amount of at least about 1% by weight, preferably at least about 2% by weight, based upon the total dry weight or dry matter of the extrudate or final product, exclusive of the encapsulant.

Generally, the plasticizable matrix material which is a source of gluten, such as wheat flour, may have a gluten content of at least about 6% by weight, based upon the weight of the plasticizable matrix material. For example, where the final product is produced from 40% by weight wheat flour having a gluten

content of about 6% by weight, and from 60% by weight non-gelatinized starch having a gluten content of essentially zero: the gluten content of the final product is about 2.4% by weight, based upon the total weight of the dry matter or the total weight of the plasticizable matrix material (wheat flour) and the total weight of the substantially non-plasticizable matrix material (non-gelatinized starch).

The relative amounts of the plasticizable matrix material and the substantially non-plasticizable matrix component may be used to control glassiness of the particles, hardness of the particles and encapsulant release rates of the particles. In embodiments of the invention, the amount of the matrix component which is substantially non-plasticizable, such as non-gelatinized starch, is at least about 10% by weight, preferably at least about 25% by weight, based upon the total weight of the at least one plasticizable matrix material and the matrix component which is substantially non-plasticizable. In embodiments of the invention, for quickest release rates, the amount of the matrix component which is substantially non-plasticizable, such as non-gelatinized starch, may be at least about 60% by weight, based upon the total weight of the at least one plasticizable matrix material and the matrix component which is substantially non-plasticizable.

Generally, as the content of the substantially non-plasticizable component increases, the amount of material in the glassy state decreases and the hardness of the final product decreases while its porosity or microporosity, penetratability, or release properties increase. For example, a matrix having 60% by weight non-gelatinized starch and 40% by weight semolina as dry matter would be more crumbly, and not as glassy or hard, as a matrix having 100% semolina as dry matter. The 60/40 blend of substantially non-plasticizable, non-gelatinized starch and plasticizable semolina would also exhibit quicker encapsulant release than the matrix having 100% by weight semolina as dry matter. Also, a matrix

having 90% by weight semolina and 10% by weight vital wheat gluten as dry matter would be more glassy and harder would release encapsulant more slowly than would the matrix having 100% by weight semolina as dry matter.

5 Plasticizers employed in the present invention may be any liquid which enables the formation of a substantially homogeneous cohesive, plasticized, viscoelastic, formable mixture, dough or crumbly mass. The liquid plasticizer is generally water but may be an aqueous-based composition such as a sugar solution, alcohol, glycerol, sorbitol, polyethylene glycol, polypropylene glycol, silicone, hexanol, pentanol, dimethylsulfoxide (DMSO), hexane, an oil, and  
10 mixtures thereof. Exemplary of edible or consumable plasticizers which may be used are water, an aqueous-based composition such as a sugar solution, juice, alcohol, glycerol, and sorbitol, oils, melted shortenings or fat, and mixtures thereof.

The liquid plasticizer contained within a liquid encapsulant component is  
15 generally water but may be an aqueous-based composition such as a sugar solution, alcohol, glycerol, sorbitol, polyethylene glycol, polypropylene glycol, silicone, hexanol, pentanol, dimethylsulfoxide (DMSO), hexane, an oil, and mixtures thereof. The liquid encapsulant component may provide at least a substantial portion or even the total amount of liquid plasticizer for forming a  
20 substantially homogeneous cohesive, plasticized, viscoelastic, formable mixture or dough. If the amount of liquid plasticizer, such as water, supplied by the liquid encapsulant component is not sufficient to obtain a formable mixture or dough at a sufficiently low temperature and under sufficiently low shear conditions so as to avoid substantial mechanical or thermal destruction of the plasticizable matrix  
25 material or encapsulant, then an additional amount of liquid plasticizer may be admixed with the other ingredients. The additional liquid plasticizer may be the same or different as the liquid plasticizer provided by the liquid encapsulant component.

The amount of liquid plasticizer, such as water and/or oil, should generally be sufficient to obtain a formable mixture or dough at a sufficiently low temperature and under sufficiently low shear conditions so as to avoid substantial mechanical or thermal destruction of the free-flowing mixture or encapsulant. Exemplary total amounts of plasticizer, such as oil and/or water, used to form a dough or crumbly mass may range up to about 90% by weight, for example from about 10% by weight to about 70% by weight, generally from about 20% by weight to about 50% by weight, preferably from about 25% by weight to about 45% by weight, based upon the total weight of the plasticizable matrix material, such as semolina, the substantially non-plasticizable matrix component, such as non-gelatinized starch, and the added plasticizer used to form the dough or crumbly mass.

If water is employed as a plasticizer, higher amounts are less desirable, because more drying may be needed to obtain a shelf-stable product. When an edible oil, shortening or fat is employed as a plasticizer, it may generally be used in higher amounts because the need for drying of the dough to obtain a shelf-stable moisture content is substantially reduced or eliminated. The addition of vegetable oil during mixing has been proven useful to obtain a smooth continuous dough phase and it facilitates forming of the dough into discrete particles. Use of an oil or fat as a plasticizer in place of or in addition to water, in addition to facilitating extrusion, also serves to provide a protective coating on the plasticizable matrix materials such as semolina, and on the encapsulant. Accordingly, the amount of oil or fat employed may be used to control the rate of release of encapsulant.

Edible oils, shortenings or and fats which may be employed include those derived from plant, animal, and marine sources such as vegetable shortening or oils, which include corn oil, safflower oil, soybean oil, and cotton seed oil, which may be hydrogenated, as well as edible fat substitutes. In embodiments of the

invention, particularly where high levels of oil or fat are employed, the melting point of the oil, shortening or fat should be sufficiently high so as to avoid separation of oil during extrusion. For example, the melting point of the oil, shortening or fat may be at least about 30°C, preferably at least about 37°C, most preferably at least about 40°C.

In embodiments of the invention, the formable mixture or dough may have a total plasticizer content, such as water and/or oil, of up to about 90% by weight, generally from about 10% by weight to about 50% by weight, for example about 15% by weight to about 25% by weight. The total plasticizer content may include water supplied by any liquid encapsulant component and additional plasticizer, such as added water, glycerol, sorbitol or a combination thereof or any other liquids, such as fruit juice, that enables the formation of a dough. When water or low melting point oils are employed at high levels, for example a moisture content well above 50%, a thin, low viscosity dough may result. The low viscosity dough may either not be formable or the drying efforts would be unnecessarily high. Substantially lower moisture contents, such as well below 5% may result in a dry product, which would be too fragile after forming and would fall apart. It may also generate frictional heat during extrusion forming which would be detrimental to the heat sensitive encapsulant. The water may be mixed with organic acids or fruit juice to adjust pH and to obtain a pleasant flavor in the final product.

The liquid plasticizer content of any liquid encapsulant component utilized may be at least about 35% by weight, generally at least about 50% by weight, for example from about 65% by weight to about 90% by weight, based upon the weight of the liquid encapsulant component.

For example, an aqueous dispersion of Lactobacillus acidophilus may have a moisture content of about 70% by weight and an encapsulant content (Lactobacillus acidophilus) of about 30% by weight. The 70% moisture content



stemming from the acidophilus dispersion may be used as a plasticizer. The ratio of the total of plasticizable matrix material and substantially non-plasticizable matrix component to moisture stemming from the aqueous encapsulant liquid may be about 3:1 to enable the formation of a homogeneous dough. Vegetable  
5 oil may be added to delay penetration of water into the matrix and delay the release of the microorganism. The encapsulation of sensitive liquid components into a matrix to obtain discrete shelf-stable particles is disclosed in U.S. patent application serial no. 09/233,443 filed January 20, 1999 in the name of Bernhard H. van Lengerich for "Encapsulation of Sensitive Liquid Components into a  
10 Matrix to Obtain Discrete Shelf-stable Particles," the disclosure of which is herein incorporated by reference in its entirety.

Additional ingredients which may be used to control the release properties of the final product may be a hydrophobic agent for slowing down the rate of release of the encapsulant. Exemplary of components which may be added to  
15 affect the hydrophobicity of the matrix include fats, oils, waxes, fatty acids, emulsifiers, such as mono- or di- glycerides, synthetic polymers such as polyolefins such as polyethylene or polypropylene, polyvinyl chloride, polyvinyl acetate and derivatives thereof, paraffin, and modified starches from plant sources that possess hydrophobic properties that are obtained via either physical  
20 or chemical modification, and mixtures of hydrophobic components. Plant lipids or synthetic lipids with melting points up to about 65°C may, for example, be employed as a hydrophobic agent. The hydrophobic components increase the hydrophobicity of the matrix and help to prevent or delay penetration of water or gastric juice into the matrix by repelling water or aqueous acids, thereby delaying  
25 the release of the encapsulant into the surrounding media.

Additional components which may be used to delay or prevent a fast release of the encapsulant from the matrix are components or agents which have a high water binding capacity. The agents may have a water binding capacity or

water holding capacity which is greater than the water binding capacity of the matrix material, such as semolina or starch. The high water binding capacity component may bind water which penetrates the particles, or prevent the water from dissolving the matrix, thereby preventing or delaying the release of the encapsulant from the matrix. Exemplary of high water binding capacity agents which may be used in the present invention are protein from animal sources such as gelatin, casein, and protein from sources such as wheat, soy, corn, or other grains, and hydrocolloids such as carrageenans, alginates, xanthan gum, gum arabic, guar flour or guar gum, agar, tragacanth, karaya, locust bean gum, pectin, soluble fiber, insoluble fiber and the like. Exemplary proteins from grains which may be used are gluten, vital wheat gluten, zein, and soy protein concentrate. The proteins from plant sources may also be used to increase the tolerable addition of lipids within the matrix composition and thereby indirectly increase the hydrophobicity of the matrix. The high water binding capacity components may be used alone or mixtures thereof may be employed.

Process compatible additional components to facilitate processing, or to improve sensory attributes such as the taste, texture, aroma, color, appearance, or hydration behavior of the final pellets which may be employed include: flavors, sodium chloride, nonfat dry milk, whey protein, high fructose corn syrup, leavening agents, lipids, such as oils or fats, chocolate liquor, chocolate, cocoa powder, compound coatings, concentrated fruit juice, or particulates, such as ground nuts or almonds. The water may be pH adjusted to obtain a good tasting product. The addition of vegetable oil during mixing has been found useful to obtain a smooth continuous dough phase and it facilitates forming of the dough and cutting into discrete particles without sticking.

The additional components or ingredients, such as those used to control the rate of release of the encapsulant may be used in amounts up to about 70% by weight, preferably from about 5% by weight to about 50% by weight, most

preferably from about 10% by weight to about 35% by weight, based upon the weight of the matrix material, such as semolina.

5 The encapsulant may be in solid and/or liquid form for inclusion in the matrix compositions and encapsulated products of the present invention. In  
embodiments of the invention, the solid encapsulant may be in powdered, particulate, granular, crystalline, or comminuted form for dry-blending with the plasticizable matrix component and the substantially non-plasticizable matrix component. The solid encapsulant may also be suspended or dispersed in a liquid plasticizer of a liquid encapsulant component. In other embodiments, the  
10 encapsulant may be dissolved in a liquid plasticizer of a liquid encapsulant component. Also, encapsulant may be provided by a liquid encapsulant component, and additional encapsulants in solid form, such as a dry powder, may be included in the encapsulated products of the present invention.

15 Active components which may be encapsulated or embedded in the matrixes in accordance with the present invention include pharmaceutical compositions or compounds, nutraceutical compositions or compounds, nutritional components, or biologically active components, flavorants, fragrances, detergents or surface-active compositions.

20 The pharmaceutical compounds or compositions and biologically active compositions may, for example, include antibiotics, analgesics, vaccines, antiinflammatory agents, antidepressants, anti-viral agents, anti-tumor agents, enzyme inhibitors, formulations containing zidovudine, macromolecular polypeptides, aromatic nitro and nitroso compounds and their metabolites useful as anti-viral and anti-tumor agents, HIV protease inhibitors, viruses, and steroids,  
25 compositions to promote growth such as hormones, or other growth stimulating agents, mixtures thereof, and the like.

Nutraceutical components may include components which promote health or prevent disease or enhance well-being such as antioxidants,

phytochemicals, hormones, vitamins such as Vitamins A, B1, B2, B6, B12, C, D, E, K, pantothenate, folic acid, pro-vitamins, minerals such as calcium, selenium, magnesium salts, available iron, and iron salts, microorganisms such as bacteria, such as live lactobacilli, fungi, and yeast, prebiotics, probiotics, trace elements, essential and/or highly unsaturated fatty acids such as omega-3 fatty acids, and mid-chain triglycerides, nutritional supplements, enzymes such as amylases, proteases, lipases, pectinases, cellulases, hemicellulases, pentosanases, xylanases, and phytases, pigments, oligopeptides, dipeptides, and amino acids, and mixtures thereof.

Biologically active components which may be encapsulated include agriculturally useful compositions to either prevent infestation such as herbicides, pesticides, insecticides, rodenticides, fungicides, mixtures thereof, and the like or to promote growth such as hormones, fertilizers, or other growth stimulating agents.

Exemplary of the active components which may be encapsulated or embedded in accordance with the present invention are: acepromazine, acetaminophen, acetohexamide, acetohydroxamic acid, acetylcholine, acetylcysteine acyclovir, albendazole, alclometasone dipropionate, allopurinol, alprazolam, alprostadiol, amcinonide, amantadine, amdinocillin, amikacin, amiloride, aminocaproic acid, aminophylline, aminosalicylate, aminosalicyclic acid, amitriptyline hydrochloride, ammonium chloride, amobarbital, amodiaquine hydrochloride, amoxapine, amoxicillin, amphetamine sulfate, amphotericin, ampicillin amprolium, acetazolamide acetyldigoxin, acetylsalicylic acid, anileridine, anthralin, antipyrine, antivenin, apomorphine, apraclonidine, ascorbic acid, aspirin, acromycin atropine, amoxycillin anipamil, azaperone, azatadine maleate, azathioprine, azithromycin, aztreonam, bacampicillin, bacitracin, baclofen, barium salts, beclomethasone dipropionate, belladonna extract, bendroflumethiazide, benoxinate hydrochloride, benzethonium chloride,

benzocaine, benzonatate benzthiazide, benztropine mesylate, betaine,  
betamethasone, betaxolol, betanechol chloride, biotin, biperiden, bisacodyl,  
bismuth, botulism antitoxin, bromocriptine mesylate, bromodiphenhydramine  
hydrochloride, bumetanide, bupivacaine, busulfan butabarbital sodium, butalbital,  
5 combinations of butalbital, caffeine and aspirin and codeine, beta-carotene,  
calcifediol, calcium carbonate, calcium citrate, calcium salts, candicidin,  
captopril, carbachol, carbamazepine, carbenicillin indanyl sodium, carbidopa,  
carbinoxamine maleate, carboprost tromethamine, carboxymethyl cellulose,  
carisoprodol, casanthranol, cascara, castor oil, cefaclor, cefadroxil, cefamandole  
10 nafate, cefazolin, cefixime, cefoperazone, cefotaxime, cefprozil, ceftazidime,  
cefuroxime axetil, cephalixin, cephradine, chlorambucil, chloramphenicol,  
chlordiazepoxide, chloroquine phosphate, chlormadinone acetate, chlorothiazide,  
chlorpheniramine maleate, chloroxylenol, chlorpromazin, chlorpropamide,  
chlorprothixene, chlorprothixene, chlortetracycline bisulfate, chlortetracycline  
15 hydrochloride, chlorthalidone, chlorzoxazone, cholecalciferol, cholera vaccine,  
chromic chloride, chymotrypsin, cimetidine, cinoxazin, cinoxate, ciprofloxacin,  
cisplatin, clarithromycin, clavulanate potassium, clemastine fumarate, clidinium  
bromide, clindamycin hydrochloride, -palmitate and -phosphate, clioquinol,  
clofazimine, clofibrate, clomiphene citrate, clonazepam, cinnarizine, clonidine  
20 hydrochloride, clorsulon, clotrimazole, cloxacillin sodium, cyanocobalamin,  
cocaine, coccidioidin, cod liver oil, codeine, colchicine, colestipol, corticotropin,  
corisone acetate, cyclacillin, cyclizine hydrochloride, cyclobenzaprine  
hydrochloride, cyclophosphamide, cycloserine, cyclosporine, cyproheptadine  
hydrochloride, cysteine hydrochloride, danazol, dapsone, dehydrocholic acid,  
25 demeclocycline, desipramine, desoximetasone, desoxycorticosterone acetate,  
dexamethasone, dexchlorpheniramine maleate, dexpanthenol,  
dextroamphetamine, dextromethorphan, diazepam, diazoxide, dibucaine,  
dichlorphenamide, dicloxacillin sodium, dicyclomine, dienestrol, diethylpropion

hydrochlorid, diethylstilbestrol, diflunisal, digitalis, dicoumarol, digitoxin,  
digoxin, dihydroergotamine, dihydrostreptomycin, dihydrotachysterol,  
dihydroxyaluminium amino acetate, dihydroxyaluminium sodium carbonate,  
diltiazem hydrochloride, dimenhydrinate, dimercaprol, diphenhydramine  
5 hydrochloride, diphenoxylate hydrochloride, diphteria antitoxin, dipyridamole,  
disopyramide phosphate, disulfiram, dobutamine hydrochloride, docusate  
calcium, docusate sodium, dopamine hydrochloride, doxepin hydrochloride,  
doxycycline, doxycycline hyclate, doxylamine succinate, dronabinol, droperidol,  
drotaverine, dydrogesterone, dyphylline, guaifenesin, enalapril maleate,  
10 analaprilat, ephedrine, epinephrine, equilin, ergocalciferol, ergoloid mesylates,  
ergonovine maleate, ergotamine tartrate, erythrityl tetranitrate, erythromycin,  
estradiol, estriol, estrogen, estrone, estropipate, ethcrynol acid, ethambutol  
hydrochloride, ethchlorvynol, ethinyl estradiol, ethionamide, ethopropazine  
hydrochloride, ethotoin, ethynodiol diacetate, etidronate disodium, etoposide,  
15 eugenol, famotidine, fenoprofen, ferrous fumarate, ferrous gluconate, ferrous  
sulfate, flucytosine, fludrocortisone acetate, flunisolide, fluocinolone acetonide,  
fluocinonide, fluorescein sodium, fluorometolone, fluorouracil, fluoxymesterone,  
fluphenazine, flurandrenolide, flurazepam, flurbiprofen, folic acid, furazolidone,  
flunitrazepam, furosemide, gemfibrozil, gentamicin, gentian violet, glutarate,  
20 glutethimide, glycopyrrolate, chorionic gonadotropin, gramicidin, griseofulvin,  
guaifenesin, guanabenz, guanadrel sulfate, halazone, haloperidol, haloprogin,  
halothane, heparin calcium, hepatitis virus vaccine, hetacillin potassium,  
hexylresorcinol, histamine phosphate, histidine, homatropine, histoplasmin,  
hydralazine hydrochloride, hydrochlorothiazide, hydrocodone bitartrate,  
25 hydrocortisone, hexobarbital, hydroflumethiazide, hydromorphone  
hydrochloride, hydroquinone, hydroxocobalamin, hydroxyamphetamine,  
hydroxychloroquine sulfate, hydroxyprogesterone caproate, hydroxyurea,  
hydroxine hydrochloride, hydroxine pamoate, hyoscyamine, hyoscyamine

sulfate, ibuprofen, ifosfamide, imipramide, imipramide hydrochloride,  
indapamide, indomethacin, insulin, inulin, iocetamid, iodoquinol, iohexol,  
iopamidol, ipecac, ipodate calcium, ipodate sodium, isocarboxacid, isoetharine  
hydrochloride, isoflurane, isoniaacid, isopropamide iodine, isoproterenol  
5 hydrochloride, isosorbide dinitrate, isotretinoin, isoxsuprine hydrochloride,  
kanamycin sulfate, ketoprofen, ketoconazole, labetalol hydrochloride, lanolin,  
leucine, leucovorin calcium, levamisole hydrochloride, levocarnithine, levodopa,  
levonorgestrel, levorphanol tartrate, levothyroxine sodium, lidocaine, lincomycin  
hydrochloride, lindane, liothyronine sodium, liotrix, lisinopril, lithium carbonate,  
10 loperamide hydrochloride, loracarbef, lonetil, lorazepam, lovastatin, loxapine,  
lysine, mafenide acetate, magaldrte, magnesium carbonate, magnesiumchloride,  
magnesium gluconate, magnesium oxide, other magnesium salts, malathionon,  
manganese salts, manganese, maprotiline hydrochloride, mazindol, measles virus  
vaccine, mebendazole, mebifenin, mecamlamine hydrochloride, meclizine  
15 hydrochloride, meclocycline , meclofenamate sodium, medroxyprogesterone  
acetate, mefenamic acid, megestrol acetate, meglumine, melphalan, menadiol  
sodium diphosphate, menadione, menotropine, meperidine, mephénytoin,  
mephobarbital, meprednisone, meprobamate, mercaptopurine, mesoridazine  
besylate, mestranol, metaproterenol sulfate, metaraminol bitartrate, methacycline  
20 hydrochloride, methadone hydrochloride, methamphetamine hydrochloride,  
methazolamide, methdilazine, methenamine, methicillin sodium, methimazole,  
methionine, methocarbamol, methotrexate, methoxsalen, methoxyflurane,  
methsuximide, methyclothiazide, methylbenzethonium chloride, methyl dopa,  
methylergonovine maleate, methylphenidate hydrochloride, methylprednisolone,  
25 methyltestosterone, methysergide maleate, metoclopramide, metolazone,  
meoprolol tartrate, metronidazole, metyrapone, metyrosine, mexiletine  
hydrochloride, mexiletine hydrochloride, miconazole, minocycline  
hydrochloride, minoxidil, mitomycin, mitotane, molindone hydrochloride,

monobenzene, morphine sulfate, mupirocin, medazepam, mefruside,  
methandrostenolone, methylsulfadiazine, nadolol, nafcillin, nafcillin sodium,  
nalidixic acid, nalorphine, naloxone, nandrolone decanoate, nandrolone  
phenpropionate, naproxen, natamycin, neomycin, neomycin sulfate, neostimine  
5 bromide, niacin, nitrofurantoin, nalidixic acid, nifedipine, nitrazepam,  
nitrofurantoin, nitroglycerine, nitromerson, nizatidine, nonoxynol 9,  
norethindrone, norethindrone acetate, norfloxacin, norgestrel, nortriptyline  
hydrochloride, noscapine, novobiocin sodium, nystatin, opium, oxacillin sodium,  
oxamniquine, oxandrolone, oxazepam, oxprenolol hydrochloride, oxtriphylline,  
10 oxybenzone, oxybutynin chloride, oxycodone hydrochloride, oxycodone,  
oxymetazoline hydrochloride, oxymetholone, oxymorphone hydrochloride,  
oxyphenbutazone, oxytetracycline, padimate, pancreatin, pancrelipase, papain,  
panthenol, papaverin hydrochloride, parachlorophenol, paramethasone acetate,  
paregoric, paromomycin sulfate, penicillamine, penicillin, penicillin derivatives,  
15 pentaerythritol tetranitrate, pentazocine, pentazocine hydrochloride, pentazocine  
salts, pentobarbital sodium, perphenazine, pertussis, phenacemide,  
phenazopyridine hydrochloride, phendimetrazine tartrate, phenelzine sulfate,  
phenmetrazine hydrochloride, phenobarbital, phenophtalein, phenoxybenzamine  
hydrochloride, phentermine hydrochloride, phenylalanine, phenylbutazone,  
20 phenylephrine hydrochloride, phenylpropanolamine hydrochloride,  
physostigmine, phytonadione, pilocarpine , pimozide, pindolol, piperazine,  
piroxicam plicamycin, poliovirus vaccine inactivated, polycarbophil, polymycin  
b sulfate, polythiazide, potassium chloride, potassium citrate, potassium  
cluconate, potassium iodine, potassium sodium tartrate, povidone iodine,  
25 pralidoxime chloride, pramoxine hydrochloride, pramezam, prazepam,  
praziquantel, prazosin hydrochloride, prazosin hydrochloride, prednisolone,  
prilocaine, primaquine, primidone, probenecid, probucol, procainamide  
hydrochlorid, procaine hydrochloride, procarbazine hydrochloride,



prochlorperazine, prochlorperazine maleate, procyclidine hydrochloride,  
progesterone, proline, promazine, promazine hydrochloride, promazine,  
promethazine, promethazine hydrochloride, propafenone hydrochloride,  
propantheline, proparacaine hydrochloride, propoxycaine hydrochloride,  
5 propoxyphene hydrochloride, propoxyphene napsylate, propanolol  
hydrochloride, propylidone, propylthiouracil, propylthiouracil, protriptyline  
hydrochloride, pseudoephedrine hydrochloride, pumice, pyrantel pamoate,  
pyrazinamide, pyrethrum extract, pyridostigmine bromide, pyridoxine  
hydrochloride, pyriline maleate, pyrimethamine, pyroxylin, pyrvinium  
10 pamoate, phenacetin, phenytoin, prednisone, uinidine gluconate, quinidine  
sulfate, rabies vaccine, racepinephrine ranitidine, rauwolfia serpentina,  
resorcinol, ribavirin, riboflavin, rifampin, ritodrine, rubella virus vaccine,  
saccharin, saccharin sodium, salicylamide, salicylic acid, salsalata, scopolamine,  
secobarbital sodium, selenius acid, selenium sulfate, sennaserine, simethicone,  
15 sodium ascorbate, sodium bicarbonate, sodium fluoride, sodium gluconate,  
sodium iodide, sodium lactate, sodium nitrite, sodium ditroprusside, sodium  
salicylate, spironolactone, stannozolol, streptomycin, sucalfate, sulfacetamide,  
sulfadiazine, reserpine, sulfadioxine, sulfamerazine, sulfamethazine,  
sulfamethizole, sulfamethoxazole, sulfamethoxydiazine, sulfapyridin,  
20 sulfasalazine, sulfaperin, sulfathiazole, sulfisoxazole, sulfinpyrazone, sulindac,  
suprofen, stilains, tamoxifen citrate, temacepam, terbutaline sulfate, terfenadine,  
terpin, testolacton, testosterone, tolazamide, tolbutamide, tetracaine, tetracycline,  
tetrahydrocycline, theophylline, thiabendazole, thiamine hydrochloride, thiamin,  
thiamylal, thiethylperazine thimerosal, thioguanine , thioridazine hydrochloride,  
25 thistrepton, thiotepa, thiothixene, threonine, thyroid, ticarcillin, timolol,  
tioconazole, titaniumdioxide, tolazamide, tolbutamide, tolmetin, tolnaftate,  
trazodone hydrochloride, tretinoin, triacetin, triamcinolone, triamterene,  
triazolam, trichorfon, trichlormethiazide, trientine hydrochloride, trifluoperazine

hydrochloride, triflupromazine, trihexyphenidyl hydrochloride, trimeprazine  
tartrate, trimethadione, trimethobenzamide hydrochloride, trimethoprim,  
trioxsalen, tripelennamine, triprolidine, trisulfapyrimidine, tropicamide, trypsin,  
tryptohan, tuberculin, tyloxapol, tyropanoate sodium, tyrosine, tyrothricin,  
5 thyrothricin bethamethasone, thiotic acid, sotalol, salbutamol, norfenefrine,  
silymarin, dihydroergotamine, buflomedil, etofibrate, indometacin, urea, valine,  
valproic acid, vancomycin hydrochloride, vasopressin, verapamil, vidarabine,  
vinblastine, vincristine, vitamins, warfarin, yellow fever vaccine, zinc acetate,  
zinc carbonate, zinc chloride, zinc gluconate, beta acetyl digoxin, piroxicam,  
10 haloperidol, ISMN, amitriptylin, diclofenac, nifedipine, verapamil, pyritinol,  
nitrendipin, doxycycline, bromhexine, methylprdnisolone, clonidine, fenofibrate,  
allopurinol, pirenepine, levothyroxin, tamoxifen, metildigoxin, o-(beta-  
hydroxyethyl)-rutoside, propicillin, aciclovir mononitrate, paracetamol,  
naftidrofuryl, pentoxifylline, propafenone, acebutolol, L-thyroxin, tramadol,  
15 bromocriptine, loperamide, ketotifen, fenoterol, cadobelisate, propanolol,  
enalaprilhydrogen maleate, bezafibrate, ISDN, gallopamil, xantinol nicotinate,  
digitoxin, flunitrazepam, bencyclane, dexapanthenol, pindolol, lorazepam,  
diltiazem, piracetam, phenoxymethylpenicillin, furosemide, bromazepam,  
flunarizin, erythromycin, metoclopramide, acemetacin, ranitidin, biperiden,  
20 metamizole, doxepin, dipotassium chlorazepate, tetrazepam, estramustine  
phosphate, terbutaline, captopril, maprotiline, prazosin, atenolol, glibenclamide,  
cefaclor, etilfrine, cimetidine, theophylline, hydromorphone, ibuprofen,  
primidone, clobazam, oxaceprol, medroxyprogesterone, flecainid, pyridoxal 5  
phosphate glutamate, hymechromone, etofylline clofibrate, vincamine,  
25 cinnarizine, diazepam, ketoprofen, flupentixol, molsimine, glibornuride,  
dimetinden, melperone, soquinolol, dihydrocodeine, clomethiazole, clemastine,  
glisoxepide, kallidinogenase, oxyfedrine, baclofen, carboxymethylcysteine,  
thioridazine, betahistine, L-tryptophan, murtol, bromelaine, prenylamine,

salazosulfapyridine, astemizol, sulpiride, benzerazide, dibenzepine,  
acetylsalicylic acid, miconazol, nystatin, ketoconazole, sodium picosulfate,  
coltyramine, gemfibrocil, rifampicin, fluocortolone, mexiletin, amoxicillin,  
terfenadrin, mucopolysaccharide polysulfate, triazolam, mianserin, tiaprofenic  
5 acid, amezinium metilsulfate, mefloquine, probucol, quinidine, carbamazepine,  
L-aspartate, penbutolol, piretanide, aescin amitriptyline, cyproterone, sodium  
valproinate, mebeverine, bisacodyl, 5-aminosalicylic acid, dihydralazine,  
magaldrate, phenprocoumon, amantadine, naproxen, carteolol, famotidine,  
methyldopa, auranofine, estriol, nadolol, levomepromazine, doxorubicin,  
10 medofenoxate, azathioprine, flutamide, norfloxacin, fendiline, prajmalium  
bitartrate, lipid derivatives of phosphonatides, amphiphilic polymers, adenosine  
derivatives, sulfated tannins, monoclonal antibodies, and metal complexes of  
water soluble texathyrin.

The amount of the active component or encapsulant which is incorporated  
15 into the products of the present invention may be such so as to provide or deliver  
an effective amount, such as a pharmaceutically effective amount or a  
nutraceutically effective amount of the active component at its intended location,  
such as the small intestine. Exemplary amounts of the active component or  
encapsulant which may be encapsulated or embedded into the matrix may be  
20 from about 1% by weight to about 85% by weight, preferably from about 3% by  
weight to about 50% by weight, most preferably from about 5% by weight to  
about 30% by weight, based upon the total weight of the plasticizable matrix  
ingredient, such as semolina, and the matrix component which is substantially  
non-plasticizable, such as non-gelatinized starch.

25 In embodiments of the invention, the encapsulants and/or the matrix  
composition may be coated to provide additional protection against oxygen, to  
provide mechanical stability against abrasion, or to control release of the  
encapsulant. Film-building or film-forming substances which may be used to

coat encapsulants prior to admixing with the plasticizable matrix material and prior to incorporation into the matrix include commonly used coating materials. Exemplary of coating materials which may be employed are zein, pectin, shellac, gelatin, gluten, fats, oils, waxes, emulsifiers, native or modified starch, chitosan, chitin, and mixtures thereof. These film-building or film-forming substances may also be used to coat the extruded, particulate product. Pretreatment of the encapsulant by coating it with a film forming substance such as a high melting fat or wax, or with an emulsifier such as glycerin monostearate, or the like, tends to prevent unwanted interaction between an encapsulant and the matrix. The encapsulants and the extrudate particles may be coated with film-forming amounts of the substances in aqueous or alcoholic solutions, or oleaginous compositions. The encapsulants may be pre-encapsulated or pre-coated using any conventional encapsulation or coating method which does not thermally destroy the encapsulant.

In embodiments of the invention pellets may be coated in a two step coating process. After discrete particles have been cut at an extrusion die, the substantially undried pellets may be coated with a first component of a composite coat, such as an acetic-acid-chitosan-solution. After this step a second coat may be applied using a gel forming counter ion, such as a polyphosphate solution, that causes the chitosan to gel and form a chitin coat. The second ion may also be provided by a pectin and the resulting composite coat may then be a pectin-chitin coacervate.

The film-forming substances or coatings may also contain additional components that protect the particulates or pellets, or encapsulant, from the influence of light, such as titanium dioxide, or cocoa-based products. The coatings may also contain anti-oxidants to protect the pellets or encapsulants from the influence of oxygen or air.

In accordance with embodiments of the present invention, the thickness of

the coating upon the encapsulant may be used to control the rate of release of encapsulant once the dissolving media, such as water, reaches the encapsulant. For example, increasing the thickness of the coating on the encapsulant slows its rate of release into the media. Also, increasing the thickness of the coating on the extrudate or pellet delays release of the encapsulant from the matrix material. In embodiments of the invention, the amount of coating may range from about 0.5% to about 50% by weight, based on weight of the total product, depending upon the desired release of the encapsulant.

In accordance with the method of the present invention, all of the ingredients may be admixed together at a temperature which does not substantially destroy the encapsulant or substantially gelatinize starch, such as temperatures of less than about 55°C, preferably less than 40°C, most preferably less than about 35°C. Exemplary temperatures which may be employed to obtain a formable mixture or dough may be about 5°C to about 50°C, for example about 30°C. Mixing or dough temperatures substantially higher than about 50°C are undesirable, because any fat or oil in the formula tends to separate, or the heat sensitive substances to be encapsulated and embedded would be destroyed. Temperatures much lower than room temperatures, such as for example 0°C are for most purposes impractical but may be employed in special applications. In embodiments of the invention, the temperature may be adjusted by external heating, below 50°C, preferably less than 40°C so as to facilitate forming and enable cutting without the material sticking to the cutter.

In embodiments of the present invention, external heating of the ingredients during their admixture is not required. Admixing of the plasticizable matrix material, such as durum wheat, with the plasticizer, such as water, a solid and/or liquid encapsulant, and a substantially non-plasticizable matrix component, such as a substantially non-gelatinized starch, may all be performed at, for example, room temperature. The admixing plasticizes the plasticizable

matrix component without substantially plasticizing the substantially non-plasticizable matrix component. Also, substantial gelatinization of the plasticizable matrix material and the substantially non-plasticizable matrix component does not occur. For example, in embodiments of the invention, the  
5 increase in the degree of gelatinization may be essentially zero or up to about 10% as measured by differential scanning calorimetry (DSC).

The resulting admixture can be compressed by extrusion through a die into a coherent, dough, capable of being cut into pellets or pieces. Drying of the compressed mixture or dough produces a weakened, porous or discontinuous  
10 glassy matrix for quicker release. However, the product possesses substantial particle strength and coherency. For example, where durum wheat is used as the plasticizable matrix material, heating of the durum wheat and water to cook or gelatinize the durum wheat is not needed to obtain a formable, extrudable mixture which can be compressed into a dough and dried into a shelf-stable  
15 coherent, cohesive, but substantially non-glassy or partially glassy matrix which is more penetratable and more crumbly than uncooked pasta. The partially glassy products are generally not chewable, but are perceived as being glassy and are pneumatically transportable without substantial dusting or disintegration.

The admixing of the ingredients is conducted under low shear mixing  
20 conditions without substantially destroying or decomposing the matrix material or encapsulant. An overall quantitative measure of the shear used inside an extruder, for example, is the specific mechanical energy input. In embodiments of the present invention, the specific mechanical input during admixing of the ingredients to obtain a formable mixture or dough may be below about 150  
25 Wh/kg, preferably below about 100 Wh/kg, and most preferably below about 50 Wh/kg.

In embodiments of the invention, the pressure under which the formable mixture or dough may be formed may range from about 1 bar to about 150 bars,

preferably from about 2 bars to about 100 bars. In embodiments of the invention, the mixture may be formed into individual shapes at pressures of about 5 bars to about 60 bars.

5 In embodiments of the invention, some or all of the dry ingredients may be preblended or dry blended and then admixed with any liquid components such as the plasticizer or a liquid encapsulant component. For example, a solid, preferably a powder, encapsulant, the substantially non-plasticizable matrix component, and at least one additional ingredient or component, such as a solid hydrophobic component, or high water binding capacity component for  
10 controlling the release properties of the final product, may be dry blended or preblended with the plasticizable matrix material such as semolina. In other embodiments of the invention, any of the dry ingredients, such as a solid encapsulant or a solid component for controlling the release properties may be added separately to an admixture of the remaining dry ingredients and the liquid  
15 plasticizer.

The solid encapsulant and/or liquid encapsulant component may be admixed with the plasticizable matrix material either before or after it is plasticized. In preferred embodiments, a solid, preferably a powder, encapsulant is dry-blended with the plasticizable matrix component, the substantially non-  
20 plasticizable matrix component and any other dry ingredients prior to admixing with a plasticizer to more readily homogeneously disperse the encapsulant throughout the matrix component and throughout the matrix.

25 In embodiments of the invention, a dough comprising all ingredients may be made using conventional batch or continuous mixers. Subsequently, the dough, which may be a crumbly dough may be fed into a single screw extruder. The single screw extruder presses the dough against a die plate and plasticizes the crumbs into a continuous dough phase which may then be pressed through an extrusion die and subsequently cut into individual particulates.

In other embodiments of the invention, the dough can be made continuously and using a continuous mixer or extruder alone. Twin screw extruders or co-rotating twin screw mixers may be advantageously used which enable the steps of continuously mixing the dough and subsequently extruding the dough through an extrusion die plate. Co-rotating intermeshing twin screw extruders, such as those available from Buhler, Switzerland, Clextral France, Werner and Pfleiderer Germany, APV England or Wenger USA, or a Co-Kneader, available from Buss, Switzerland may be employed

For feeding solid components to an extruder, conventional solids feeding devices such as a volumetric or gravimetric feeder may be used. Liquid injection nozzles may be used for injecting liquid active components or solutions, dispersions, emulsions or suspensions. In embodiments of the invention, a side feeder and liquid injection nozzles may be employed. If an injection nozzle is used, the pressure for injecting the liquid encapsulant should be sufficiently higher than the pressure in the extruder so that the encapsulant can be injected into the extruder barrel. For example, if the pressure of the plasticized mass inside the extruder is 10 bars, the injection pressure may be about 2 to about 5 bars higher, i.e. 12 to 15 bars.

In embodiments where an encapsulant is pre-coated with a film-building material or coating material, the coating material may be applied in conventional manner such as by spraying or enrobing using conventional coating equipment. Commercially available pre-coated active ingredients, such as precoated minerals or vitamins may be employed.

The admixing of the added active ingredients or encapsulants inside the extruder may be accomplished by using an appropriate extrusion screw configuration for achieving low shear mixing. For example, a combination of alternating small pitch conveying elements with distributive mixing elements, that are staggered at an angle to each other for providing axially oriented leakage



flow inside the extruder barrel may be employed. The combination of alternating conveying elements with distributive mixing elements cause the material flow to be continuously interrupted without shearing of the mass thus resulting in mixing of the material at low mechanical energy input.

5 In other embodiments of the invention, other extruder screw configurations may be used that facilitate low shear distributive mixing, such as screw elements of the type ZME, TME, SME, and so-called IGEL elements commercially available from Werner and Pfleiderer.

10 The total length of the distributive mixing section may be about 3 to 12 l/d, preferably about 4 to 6 l/d to sufficiently admix and distribute and embed or encapsulate the added active components in the matrix.

The at least substantially homogeneous mixture of plasticized matrix material, substantially non-plasticizable matrix component, and added active ingredient or encapsulant may then be conveyed towards an extruder die plate.

15 The conveying may be achieved by the use of low pitch extruder screw conveying elements which build up sufficient pressure prior to extruding the mix so that it can be forced through the apertures in the die plate. Another function of the low pitch elements is that they increase the degree of fill inside the last extruder barrel section. The increased degree of fill enables control of the  
20 temperature profile of the mix inside the extruder barrel for achieving optimum viscosity adjustment and extrusion through the subsequent die openings.

25 The dough or crumbly mass or mix may be extruded, pressed or compressed through extrusion dies having aperture diameters of from about 0.10 mm to about 4 mm, generally less than about 1mm, preferably from about 0.25 mm to about 1.0 mm. The diameter of the extrudate rope and product may be larger than the diameter of the die apertures due to deformation or swelling as the composition exits the die. The increase in diameter upon exiting the die may occur without substantial development of an expanded, puffed, foamy, or cellular

structure. The extruded rope may have a cross-sectional diameter of from about 0.15 mm to about 5 mm, preferably from about 0.15 mm to about 4 mm, most preferably from about 0.25 mm to about 1.0 mm.

5 Critical is the rate of extrudate per die area, which should be less than about 5 kg/h per mm<sup>2</sup>, preferably less than 3 kg/h per mm<sup>2</sup> and most preferably less than about 0.5 kg/h per mm<sup>2</sup>. High rates will result in high shear rates inside the die that will cause increased viscous dissipation, pressure and temperatures which may adversely affect the encapsulant and may lead to unwanted product expansion.

10 The extrudate rope may be cut at the die face using a rotating cutter, pelletizer, or rotating knives. In other embodiments, the extrudate rope may be cut away from the die using conventional cutting or forming means for producing pellets or tablets. The cut pieces, pellets, or tablets, may have a length:diameter ratio (l/d ratio) of about 0.5 to 10, preferably about 1.

15 In accordance with the process of the present invention, the particle size may be varied to control the surface to volume ratio of the pellets or pieces for achieving a desired controlled release of the encapsulant. The particle size may be varied, for example, by the use of different diameters for the extrusion die openings. Particle size may also be varied by the use of a variable speed cutter  
20 either at the die plate at the end of the extruder or away from the extruder after the ropes have been conveyed for a short distance. By varying the speed of the cutter, the size of the cut pieces may be varied for a given extruder throughput. The use of a variable cutter which is spaced a short distance from the die plate, for example, between about 0.5 meters to about 5 meters permits further surface  
25 cooling, further surface drying, and reduced stickiness to provide better cutting of the ropes into pellets.

In producing products for human or animal consumption, variation of particle size to control the surface to volume ratio of the pellets is critical for

achieving a controlled release of the encapsulant during passage of the pellets or particles through the mouth, the stomach, and the intestine. Variation of particle size is also critical for controlling the residence time of the pellets inside the stomach. For example, particles smaller than 1 mm pass through the stomach or intestine faster than would particles larger than for example 2.5 mm.

After cutting, the resulting pieces or pellets may be dried to a sufficiently low moisture content which assures a sufficiently prolonged storage stability or shelf life. For example, the pellets may be dried to achieve a storage stability or shelf life of at least about six months, preferably at least about twelve months, most preferably at least about thirty-six months. In embodiments of the present invention, the drying may be performed using conventional drying equipment using drying temperatures which do not adversely affect the thermal stability of the encapsulants. Generally, the drying conditions are such that no or substantially no gelatinization of starch occurs during drying, but the drying results in a partially glassy matrix and partially glassy appearance. Exemplary drying temperatures may range from about 10°C to about 50°C, for example from about 20°C to about 30°C. The drying may be conducted to achieve a moisture content of less than about 30% by weight, preferably less than about 12% by weight, most preferably less than about 10% by weight, for example less than about 8% by weight. In embodiments where no starch or substantially no starch is used as a matrix material, the moisture content may be less than about 6% by weight.

The product may be dried using a conventional fluidized bed or other conventional drying means. The product may be optionally coated after drying using conventional coating equipment such as coating pans, coating drums, or spray devices.

In embodiments where film-building substances or coatings are applied to the particles or pellets, conventional spray nozzles may be located close to the

die or for spraying an aqueous or alcoholic solution of the film-building substances onto the cut pieces as they fall downwardly from the extruder die. In other embodiments, the film-building substances may be applied after drying of the pellets. For example, the film-building substances may be applied using  
5 spray nozzles, conventionally known fluid bed coating apparatus, or other conventional coating apparatus and methods. If the application of the film-building substances increases the moisture content above a shelf stable level, the water or other volatile media may be removed from the surface of the particles by additional drying.

10 In embodiments of the present invention, the extruded pieces or pellets may be compressed in conventional tablet presses to obtain compressed versions of the extruded pellets.

In other embodiments of the present invention, the mixture may be extruded or formed into bars or into a rope which may be cut into food bar-sized  
15 pieces. The mixture may also be extruded through a sheeting die into a sheet. The extruded sheet may then be cut or molded into individual pieces, such as bars, snack-sized pieces, tablets, or disks, using a rotary die or rotary cutter, or reciprocating cutter or counterrotating drums conventionally known as agglomeration drums or tableting drums.

20 The products of the present invention may possess a substantially non-chewable texture, which is perceived as being glassy or fracturable, but is between the chewable texture of streusel or chewable vitamin pills, and the dense, hard glassy texture of uncooked pasta. The products may comprise food bar or snack-sized pieces, or they may comprise discrete particles which may be  
25 spherical, lens-shaped, or flat discs having diameters of from about 0.15 mm to about 5 mm, preferably from about 0.15 mm to about 4 mm, most preferably from about 0.25 mm to about 1.0 mm, exclusive of any optional exterior film-building substances or coatings. In embodiments of the invention, the particles

about 36°C to about 38°C. Upon exiting the die, the exiting ropes may be cut with rotating knives into discrete particles of 0.5 - 1.5 mm length and air dried for about 30 minutes to obtain shelf-stable pellets which contain encapsulated and protected active phytase.

5

### EXAMPLE 3

#### Encapsulated and Protected Enzyme, Continuous Process:

A dry matrix blend consisting of 35 parts semolina, 25 parts wheat gluten, and 35 parts commercial, non-gelatinized wheat starch may be fed into a feed port of a Werner & Pfleiderer twin screw extruder at a rate of about 2.5 kg/hr. Vegetable oil may be fed at a rate of about 0.29 kg/hr and water at a rate of about 0.06 kg/hr into the same barrel of the twin screw extruder. Liquid encapsulant (about 70 wt. % water), comprising the enzyme phytase and water, may be fed at a rate of about 0.82 kg/hr into the same port of the twin screw extruder. All barrels of the extruder may be kept at a temperature of 21 °C. The die may consist of 40 circular openings, each 0.5 mm in diameter. On a calculated basis, the rate of extrudate per die area is 0.468 kg/hr per mm<sup>2</sup>. At a screw speed of about 67 rpm, the above ingredients may be mixed, conveyed and formed into a dough that may be extruded through the die openings at a pressure of about 92 bar and a product temperature of about 39°C. Upon exiting the die, the exiting ropes may be cut with rotating knives into discrete particles of 0.5 - 1.5 mm length and air dried for about 30 minutes to obtain shelf-stable pellets which contain encapsulated and protected active enzyme.

### EXAMPLE 4

#### Example of an Encapsulated and Protected Enzyme, Batch Process:

A matrix blend consisting of 29 parts semolina, 6 parts wheat gluten, and 29 parts commercial, non-gelatinized wheat starch may be preblended and mixed

with 11 parts of vegetable oil in a mixer for 3 minutes. Then 22 parts of liquid encapsulant (about 70% by weight water) comprising the enzyme phytase and subsequently 3 parts water may be added and mixed for 12 minutes to obtain a blend. The blend may then be extruded through extrusion dies having a diameter of about 0.65mm using a single screw extruder. The blend may be formed into a dough that can be extruded at about 90 bar and at a temperature of about 37°C. Upon exiting the die, the product may be cut with rotating knives into discrete particles of about 0.5 mm to about 1 mm in length and air dried for about 30 minutes to obtain shelf-stable pellets which contain encapsulated enzyme.

#### EXAMPLE 5

##### Encapsulated and Protected *Lactobacillus*:

A dry matrix blend consisting of 35 parts semolina, 25 parts wheat gluten, and 35 parts commercial, non-gelatinized wheat starch may be fed into a feed port of a Werner & Pfleiderer twin screw extruder at a rate of 2.5 kg/hr.

Vegetable oil may be fed at a rate of 0.29 kg/hr and water at a rate of 0.06 kg/hr into the same barrel of the twin screw extruder. Liquid encapsulant (about 80 wt. % water), comprising the microorganism *lactobacillus acidophilus* and water, may be fed at a rate of 0.82 kg/hr into the same port of the twin screw extruder. All barrels of the extruder may be kept at a temperature of 21°C. The die may have 40 circular openings, each 0.5 mm in diameter. On a calculated basis, the rate of extrudate per die area is 0.468 kg/hr per mm<sup>2</sup>. At a screw speed of 67 rpm, the above ingredients may be mixed, conveyed and formed into a dough and extruded through the die openings at a product temperature of less than 40°C. Upon exiting the die, the exiting ropes may be cut with rotating knives into discrete particles of 0.5 - 1.5 mm length and dried for about 30 minutes either in a vacuum drier or under CO<sub>2</sub> or another inert gas to prevent the

**EXAMPLE 1**Encapsulated and Protected Powdered *Lactobacillus*, Continuous Process:

The ingredients and their relative amounts which may be used to produce an encapsulated product in accordance with the present invention are:

INGREDIENT	PARTS BY WEIGHT	% BY WEIGHT
Semolina	200	25.5
Fat	35	4.5
Wheat Starch (commercial, non-gelatinized)	300	38.2
<i>Lactobacillus acidophilus</i> (powder)	100	12.7
Water	150	19.1
TOTAL	785	100.0

The semolina, fat, commercially available non-gelatinized wheat starch, and the powdered *lactobacillus acidophilus* may be blended to obtain a substantially homogeneous dry blend. The dry blend and the water may be separately fed into a feed port of a Werner & Pfleiderer twin screw extruder at a total rate of about 2.5 kg/hr. The pressure at the extruder inlet may be atmospheric. All barrels of the extruder may be kept at a barrel temperature of about 21 °C. The extruder die may consist of 40 circular openings, each 0.5 mm in diameter. On a calculated basis, the rate of extrudate per die area is 0.318 kg/hr per mm<sup>2</sup>. The above ingredients may be mixed, conveyed and formed into a dough at a screw speed of about 67 rpm. The dough may be extruded through the die openings at a pressure of about 92 bar and a product temperature at the die of about 39°C. Upon exiting the die, the exiting ropes may be cut with rotating knives into discrete particles of 0.5 - 1.5 mm length and air dried for

about 30 minutes to obtain shelf-stable pellets which contain encapsulated and protected active *lactobacillus acidophilus*.

### EXAMPLE 2

#### Encapsulated and Protected Enzyme, Continuous Process:

5           The ingredients and their relative amounts which may be used to produce an encapsulated product in accordance with the present invention are:

INGREDIENT	PARTS BY WEIGHT	% BY WEIGHT
Semolina	200	26.7
Fat	30	4.0
Wheat Starch (commercial, non-gelatinized)	300	40.0
Liquid Enzyme Component (80% by weight water and 20% by weight phytase)	220	29.3
TOTAL	750	100.0

15           The semolina, fat, and commercially available non-gelatinized wheat starch, may be blended to obtain a substantially homogeneous dry blend. The dry blend and the liquid encapsulant component may be separately fed into a feed port of a Werner & Pfleiderer twin screw extruder at a total rate of about 2.5 kg/hr. The pressure at the extruder inlet may be atmospheric. All barrels of the extruder may be kept at a barrel temperature of about 21 °C. The extruder die may consist of 40 circular openings, each 0.5 mm in diameter. On a calculated basis, the rate of extrudate per die area is 0.318 kg/hr per mm<sup>2</sup>. The above ingredients may be mixed, conveyed and formed into a dough at a screw speed of about 67 rpm. The dough may be extruded through the die openings at a pressure of about 95 bar to about 98 bar and a product temperature at the die of



of the invention may be in the form of tablets with diameters of up to about 10 mm. The length-to-diameter ratio (l/d) of the particles may be from about 0.1 to about 10, for example about 0.5 to about 2, preferably about 1. The particles are generally uniform in size, partially glassy, and granular to increase palatability to humans and animals in a substantially compact form that is easy to swallow with or without chewing. The products of the invention are non-expanded, generally not leavenable, and exhibit a non-puffed, substantially non-cellular, and partially glassy structure. The starch component of the matrices may be substantially ungelatinized or partially gelatinized, and not substantially destructurized or dextrinized. Exemplary specific densities of the products of the present invention are between about 800 g/liter and about 1500 g/liter (about 0.8 to about 1.5 g/cm<sup>3</sup>).

The encapsulated products of the present invention may be incorporated with or without grinding into foods intended for human or animal consumption such as baked goods, for example, bread, wafers, cookies, crackers, pretzels, pizza, and rolls, ready-to-eat breakfast cereals, hot cereals, pasta products, snacks such as fruit snacks, salty snacks, grain-based snacks, and microwave popcorn, dairy products such as yoghurt, cheese, and ice cream, sweet goods such as hard candy, soft candy, and chocolate, beverages, animal feed, pet foods such as dog food and cat food, aqua-culture foods such as fish food and shrimp feed, and special purpose foods such as baby food, infant formulas, hospital food, medical food, sports food, performance food or nutritional bars, or fortified foods, food preblends or mixes for home or food service use, such as preblends for soups or gravy, dessert mixes, dinner mixes, baking mixes such as bread mixes, and cake mixes, and baking flour.

In preferred embodiments, the active encapsulant is either a live microorganism, enzyme, micronutrient, trace element, nutraceutical component, biologically or pharmaceutically active material or a combination thereof. The

encapsulated product may be redispersed as a liquid, or as a solid for human food, animal feed, or pharmaceutical purposes. The products of the present invention may be used as or incorporated into foods for special purposes, such as performance foods, mood foods, medical foods, nutritional snacks or  
5 supplements, sport foods such as power bars, baby foods, toddler foods, infant foods, or foods for pharmaceutical purposes or other dietetic purposes. The discrete particulates or granules of the present invention may be used as a topping for breakfast cereals, snacks, soups, salad, cakes, cookies, crackers, puddings, desserts or ice cream. They may also be used as a granular ingredient  
10 for yogurts, desserts, puddings, custards, ice cream or other pasty or creamy foods. Regularly sized pieces may be individually packaged or used as nutritional snacks or, for example added to or formed into nutritional food in bar form.

The present invention is further illustrated by the following non-limiting  
15 examples where all parts, percentages, proportions, and ratios are by weight, and all temperatures are in °C unless otherwise indicated:

access of oxygen to obtain shelf-stable pellets which contain encapsulated and protected active live microorganisms.

### EXAMPLE 6

#### Example of an Encapsulated and Protected Enzyme, Batch Process:

5           34 parts semolina and 34 parts commercially available, non-gelatinized  
corn starch may preblended and mixed with 11 parts of vegetable oil in a mixer  
for 3 minutes. Then, 14 parts of liquid encapsulant comprising about 20% of the  
enzyme phytase and 80% water and subsequently 7 parts water may be added  
and mixed for 12 minutes to obtain a blend. The blend may then be extruded at  
10       60 rpm. The extrusion temperature may be about 37°C. Upon exiting the die,  
the product may be cut into discrete particles and dried at 35°C to about 6%  
moisture to obtain shelf-stable pellets which contain encapsulated enzyme. The  
loss of enzyme activity after encapsulation may be less than 5%, based upon the  
enzyme activity units per gram of added enzyme.

What is claimed is:

1. A method for encapsulating or embedding a component in a matrix comprising:
  - a. obtaining a formable mixture by admixing ingredients comprising at least one plasticizable matrix material, a liquid plasticizer, an encapsulant, a matrix component which is substantially non-plasticizable at temperatures lower than the decomposition temperature of the encapsulant, and at least one component for controlling the rate of release of the encapsulant, wherein said plasticizable matrix material is plasticizable by said liquid plasticizer at a temperature which does not substantially destroy said encapsulant, said admixing being under low shear and low temperature conditions to plasticize the plasticizable material without substantially destroying the encapsulant and without substantially gelatinizing or cooking the plasticizable matrix material to obtain a substantially homogeneous, formable mixture,
  - b. forming said formable mixture into pieces, and
  - c. drying said pieces.
2. A method as claimed in claim 1 wherein said at least one plasticizable matrix material, said encapsulant, and said matrix component which is substantially non-plasticizable are dry blended, and said plasticizable matrix material is plasticizable by said plasticizer at a temperature of less than about 35°C.
3. A method as claimed in claim 1 wherein all of the ingredients are admixed together at a temperature of about 5°C to about 50°C to obtain said formable mixture.

4. A method as claimed in claim 2 wherein said liquid plasticizer is admixed with the dry blended ingredients to plasticize said plasticizable matrix material without external heating.

5. A method as claimed in claim 1 wherein said encapsulant is a solid.

6. A method as claimed in claim 1 wherein the substantially non-plasticizable matrix component is selected from the group consisting of at least substantially non-gelatinized starch, carbohydrates which have a lower molecular weight than starches, fiber, cellulose, and hemi-cellulose.

7. A method as claimed in claim 1 wherein said matrix component which is substantially non-plasticizable is a solid, inert material which increases the rate of release of the encapsulant from the matrix.

8. A method as claimed in claim 1 wherein the amount of said matrix component which is substantially non-plasticizable is at least about 10% by weight, based upon the total weight of said at least one plasticizable matrix material and said matrix component which is substantially non-plasticizable.

9. A method as claimed in claim 1 wherein the amount of said matrix component which is substantially non-plasticizable is at least about 60% by weight, based upon the total weight of said at least one plasticizable matrix material and said matrix component which is substantially non-plasticizable.

10. A method as claimed in claim 1 wherein said substantially non-plasticizable matrix component comprises a sugar or a starch hydrolyzate.

11. A method as claimed in claim 1 wherein said substantially non-plasticizable matrix component comprises an at least substantially non-gelatinized starch.

12. A method as claimed in claim 1 wherein said at least one plasticizable matrix material comprises a durum ingredient.

13. A method as claimed in claim 12 wherein said durum ingredient comprises semolina.

14. A method as claimed in claim 1 wherein a liquid encapsulant component which contains an active, sensitive encapsulant dissolved or dispersed in a liquid plasticizer is admixed with said at least one plasticizable matrix material.

15. A method as claimed in claim 1 wherein said admixing is conducted at a temperature of less than or equal to about 35°C.

16. A method as claimed in claim 1 wherein said encapsulant is coated with a film-forming material prior to admixing with said plasticizable matrix material.

17. A method as claimed in claim 1 wherein said encapsulant comprises at least one member selected from the group consisting of enzymes, vitamins, micronutrients, and live microorganisms.

18. A method as claimed in claim 1 wherein an oil or fat is admixed with said plasticizable matrix material for controlling the rate of release of said encapsulant from the matrix.

19. A method as claimed in claim 1 wherein said plasticizable matrix material comprises at least one member selected from the group consisting of high gluten content flours, gluten from wheat, durum wheat, durum semolina, pregelatinized starch, pentosans, and hydrocolloids.

20. A method for encapsulating or embedding a solid component in a matrix comprising:

- a. obtaining a formable mixture by admixing ingredients comprising at least one plasticizable matrix material, a plasticizer, a solid encapsulant, and an additional component selected from the group consisting of at least substantially non-gelatinized starch, carbohydrates which

have a lower molecular weight than starches, fiber, cellulose, or hemi-cellulose for controlling the rate of release of the encapsulant, wherein said plasticizable matrix material is plasticizable by said liquid plasticizer at a temperature which does not substantially destroy said encapsulant, said admixing being under low shear and low temperature conditions to plasticize the plasticizable material without substantially destroying the encapsulant to obtain a substantially homogeneous, formable mixture,

- b. forming said formable mixture into pieces, and
- c. drying said pieces.

21. A method as claimed in claim 20 wherein said admixing is conducted in an extruder to obtain a substantially homogeneous mixture which is compressed into a plasticized, viscoelastic formable mixture within the extruder, and is extruded through extruder die passages and cut to obtain said pieces.

22. A method for encapsulating or embedding a solid component in a matrix comprising:

- a. obtaining a formable mixture by admixing ingredients comprising at least one plasticizable matrix material, a liquid plasticizer, a solid encapsulant, a matrix component which is substantially non-plasticizable at temperatures lower than the decomposition temperature of the encapsulant, and at least one component for controlling the rate of release of the encapsulant, wherein said plasticizable matrix material is plasticizable by said liquid plasticizer at a temperature which does not substantially destroy said encapsulant, said admixing being under low shear and low

temperature conditions to plasticize the plasticizable material without substantially destroying the encapsulant to obtain a substantially homogeneous, formable mixture,

- b. forming said formable mixture into pieces, and
- c. drying said pieces.

23. A method as claimed in claim 22 wherein said at least one plasticizable matrix material, said solid encapsulant, and said matrix component which is substantially non-plasticizable are dry blended.

24. A method as claimed in claim 22 wherein all of the ingredients are admixed together at a temperature of about 5°C to about 50°C to obtain said formable mixture.

25. A method as claimed in claim 23 wherein said liquid plasticizer is admixed with the dry blended ingredients to plasticize said plasticizable matrix material without external heating.

26. A method as claimed in claim 22 wherein all of the ingredients are admixed together without cooking or without substantially gelatinizing starch to obtain said formable mixture.

27. A method as claimed in claim 22 wherein said matrix component which is substantially non-plasticizable increases the penetrability or porosity of the matrix.

28. A method as claimed in claim 22 wherein said matrix component which is substantially non-plasticizable is a solid, inert material which increases the rate of release of the encapsulant from the matrix.

29. A method as claimed in claim 22 wherein said at least one plasticizable matrix material is plasticized by said plasticizer at room temperature.

30. A method as claimed in claim 29 wherein said at least one plasticizable matrix material turns glassy upon drying, and said matrix



component which is substantially non-plasticizable increases the porosity of the matrix.

31. A method as claimed in claim 23 wherein said at least one component for controlling the rate of release of the encapsulant is admixed with the dry blended ingredients.

32. A method as claimed in claim 23 wherein all of the ingredients are admixed together at a temperature of less than or equal to 35°C to obtain said formable mixture.

33. A method as claimed in claim 22 wherein the substantially non-plasticizable matrix component is selected from the group consisting of at least substantially non-gelatinized starch, carbohydrates which have a lower molecular weight than starches, fiber, cellulose, and hemi-cellulose.

34. A method as claimed in claim 22 wherein the substantially non-plasticizable matrix component comprises an at least substantially non-gelatinized starch, said plasticizable matrix material comprises semolina, and said at least one component for controlling the rate of release of the encapsulant comprises a fat or oil.

35. A method as claimed in claim 22 wherein a liquid encapsulant component which contains said encapsulant dispersed in said liquid plasticizer is admixed with said at least one plasticizable matrix material.

36. A method as claimed in claim 22 wherein said encapsulant component comprises at least one member selected from the group consisting of enzymes, vitamins, micronutrients, and live microorganisms.

37. An edible product for human or animal consumption comprising an encapsulated product, said encapsulated product being obtained by admixing at least one plasticizable matrix material, a liquid plasticizer, an encapsulant, a matrix component which is substantially non-plasticizable at temperatures lower than the decomposition temperature of the encapsulant, and at least one

component for controlling the rate of release of the encapsulant, wherein the substantially non-plasticizable matrix component comprises an inert material which increases the porosity of the matrix to permit quicker release of the encapsulant from the matrix, said plasticizable matrix material comprises at least one member selected from the group consisting of high gluten content flours, gluten from wheat, durum wheat, durum semolina, pregelatinized starch, pentosans, and hydrocolloids, and said encapsulant comprises at least one member selected from the group consisting of enzymes, vitamins, micronutrients, and live microorganisms.

38. An edible product as claimed in claim 37 which is a baking mix, a grain-based snack, yoghurt, popcorn, cereal, pet food, or animal feed.

39. An agricultural product or pesticide comprising an encapsulated product obtained by the method of claim 22.

40. A pharmaceutical composition comprising an encapsulated product obtained by the method of claim 22.

41. A home or personal care product comprising an encapsulated product obtained by the method of claim 22.

42. An edible product obtained by the method of claim 1.

43. An edible product obtained by the method of claim 22.

44. A method as claimed in claim 1 wherein the formable mixture is extruded through a die having multiple apertures at a rate of extrudate per die area of less than about 5 kg/h per mm<sup>2</sup>.

45. A method as claimed in claim 44, wherein the rate of extrudate per die area is less than 3 kg/h per mm<sup>2</sup>.

46. A method as claimed in claim 45, wherein the rate of extrudate per die area is less than 0.5 kg/h per mm<sup>2</sup>.

47. A method as claimed in claim 44, wherein the diameter of the apertures is from about 0.1 mm to about 4 mm.

48. A method as claimed in claim 47, wherein the diameter of the apertures is from about 0.25 mm to about 1 mm.
49. A method as claimed in claim 21 wherein the formable mixture is extruded through a die having multiple apertures to obtain an extrudate at a rate of extrudate per die area of less than about 5 kg/h per mm<sup>2</sup>.
50. A method as claimed in claim 49, wherein the rate of extrudate per die area is less than 3 kg/h per mm<sup>2</sup>.
51. A method as claimed in claim 50, wherein the rate of extrudate per die area is less than about 0.5 kg/h per mm<sup>2</sup>.
52. A method as claimed in claim 49, wherein the diameter of the apertures is from about 0.1 mm to about 4 mm.
53. A method as claimed in claim 52, wherein the diameter of the apertures is from about 0.25 mm to about 1 mm.
54. A method as claimed in claim 22 wherein the formable mixture is extruded through a die having multiple apertures to obtain an extrudate at a rate of extrudate per die area of less than about 5 kg/h per mm<sup>2</sup>.
55. A method as claimed in claim 54, wherein the rate of extrudate per die area is less than 3 kg/h per mm<sup>2</sup>.
56. A method as claimed in claim 55, wherein the rate of extrudate per die area is less than about 0.5 kg/h per mm<sup>2</sup>.
57. A method as claimed in claim 54, wherein the diameter of the apertures is from about 0.1 mm to about 4 mm.
58. A method as claimed in claim 57, wherein the diameter of the apertures is from about 0.25 mm to about 1 mm.
59. A method as claimed in claim 55, wherein the diameter of the apertures is from about 0.25 mm to about 1 mm.
60. A method for encapsulating or embedding a component in a matrix comprising:

- a. obtaining a formable mixture by admixing ingredients comprising at least one plasticizable matrix material, an encapsulant, a liquid plasticizer, a matrix component which is substantially non-plasticizable at temperatures lower than the decomposition temperature of the encapsulant, and at least one component for controlling the rate of release of the encapsulant, wherein said plasticizable matrix material is plasticizable by said liquid plasticizer at a temperature which does not substantially destroy said encapsulant, said admixing being under low shear and low temperature conditions to plasticize the plasticizable material without substantially destroying the encapsulant and without substantially plasticizing the non-plasticizable material to obtain a substantially homogeneous, formable mixture, and
- b. forming said formable mixture into pieces by extruding the formable mixture through a die having multiple apertures at a rate of extruded mixture per apertures area of less than about 5 kg/h per mm<sup>2</sup>.

61. A method as claimed in claim 60, wherein the diameter of the apertures is from about 0.1 mm to about 4 mm.

62. An edible product obtained by the process of claim 61.

63. An edible product as claimed in claim 62, wherein said edible product is pet food or animal feed.

64. An edible product as claimed in claim 37, wherein said at least one plasticizable matrix material comprises a durum ingredient, said encapsulant comprises a live microorganism or an enzyme; and said substantially non-plasticizable matrix component comprises substantially non-gelatinized starch.

65. An edible product as claimed in claim 37, wherein said at least one plasticizable matrix material comprises a durum ingredient, and said encapsulant comprises an enzyme.

66. An edible product as claimed in claim 37, wherein said admixing is conducted in an extruder to obtain a substantially homogeneous formable mixture, and said formable mixture is extruded through an extruder die having multiple apertures having a diameter from about 0.1 mm to about 4 mm to obtain an extrudate at a rate of extrudate per die area of less than about 5 kg/h per mm<sup>2</sup>.

67. An edible product as claimed in claim 66, wherein said product is pet food or animal feed.

68. A method for producing pet food or animal feed comprising:

- a. obtaining a formable mixture by admixing ingredients comprising at least one plasticizable matrix material, an encapsulant, a liquid plasticizer, a matrix component which is substantially non-plasticizable at temperatures lower than the decomposition temperatures of the encapsulant, and at least one component for controlling the rate of release of the encapsulant, wherein said plasticizable matrix material is plasticizable by said liquid plasticizer at a temperature which does not substantially destroy said encapsulant, said admixing being under low shear and low temperature conditions to plasticize the plasticizable material without substantially destroying the encapsulant to obtain a substantially homogeneous formable mixture, and
- b. forming said formable mixture into pieces by extruding the formable mixture through a die having multiple apertures having a diameter from about 0.1 mm to about 4 mm, at a

rate of extruded mixture per apertures area of less than about 5 kg/h per mm<sup>2</sup>;

wherein said at least one plasticizable matrix material comprises a durum ingredient, said encapsulant comprises live microorganisms, or enzymes; and said substantially non-plasticizable matrix component comprises substantially non-gelatinized starch.

69. A method as claimed in claim 1, wherein the amount of said at least one plasticizable matrix material is at least about 30 % by weight, based upon the weight of the dried pieces.

70. A method as claimed in claim 20, wherein the amount of said at least one plasticizable matrix material is at least about 30 % by weight, based upon the weight of the dried pieces.

71. A method as claimed in claim 22, wherein the amount of said at least one plasticizable matrix material is at least about 30 % by weight, based upon the weight of the dried pieces.

72. An edible product as claimed in claim 37, wherein the amount of said matrix component which is substantially non-plasticizable is at least about 60 % by weight, based upon the total weight of said at least one plasticizable matrix material and said matrix component which is substantially non-plasticizable.

73. An edible product as claimed in claim 72, wherein said encapsulant comprises at least one enzyme, and said plasticizable matrix material is selected from the group consisting of high gluten content flours, gluten from wheat, durum wheat, and durum semolina, and said substantially non-plasticizable matrix component comprises an at least substantially non-gelatinized starch.

74. A method as claimed in claim 1, wherein said plasticizable matrix material is selected from the group consisting of high gluten content flours, gluten from wheat, durum wheat, and durum semolina, and said substantially

non-plasticizable matrix component comprises an at least substantially non-gelatinized starch.

75. A method as claimed in claim 20, wherein said plasticizable matrix material is selected from the group consisting of high gluten content flours, gluten from wheat, durum wheat, and durum semolina, and said substantially non-plasticizable matrix component comprises an at least substantially non-gelatinized starch.

76. A method as claimed in claim 22, wherein said plasticizable matrix material is selected from the group consisting of high gluten content flours, gluten from wheat, durum wheat, and durum semolina, and said substantially non-plasticizable matrix component comprises an at least substantially non-gelatinized starch.

77. A method as claimed in claim 74, wherein all of said ingredients are admixed together at a temperature of less than or equal to 35°C to obtain said formable mixture.

78. A method as claimed in claim 75, wherein all of said ingredients are admixed together at a temperature of less than or equal to 35°C to obtain said formable mixture.

79. A method as claimed in claim 76, wherein all of said ingredients are admixed together at a temperature of less than or equal to 35°C to obtain said formable mixture.

80. A method as claimed in claim 74, wherein said formable mixture is extruded by a single screw or twin screw extruder to obtain an encapsulated product in substantially non-expanded, particulate form.

81. A method as claimed in claim 74, wherein said formable mixture is obtained by admixing said ingredients in an extruder and the formable mixture is extruded from the extruder to obtain an encapsulated product in substantially non-expanded, particulate form.

**THIS PAGE BLANK (USPTO)**



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US00/22529

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : C12N 11/10; B01J 13/02

US CL : 427/213.3; 435/182

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 427/213.3; 435/182

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
none

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WEST

search terms: encapsula\$, wheat, gel\$, fat, semolina, bacteria, starch, coating, layer, plasticiz\$

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4,242,219 A (BOGERMAN et al.) 30 December 1980, see entire document	1-81
Y	US 3,962,416 A (KATZEN) 08 June 1976, see entire document.	1-81
Y	US 5,183,690 A (CARR et al.) 02 February 1993, see entire document.	1-81
Y	WO 98/18610 A1 (VAN LINGERICH, B.) 07 May 1998	1-81

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* "A"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*E"	earlier document published on or after the international filing date	*X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*O"	document referring to an oral disclosure, use, exhibition or other means	*Z* document member of the same patent family
*P"	document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

07 NOVEMBER 2000

Date of mailing of the international search report

28 NOV 2000

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

KEITH D. HENDRICKS

Telephone No. (703) 308-0661

**THIS PAGE BLANK (USPTO)**